


e Sounds

"High-quality sound, Reproduce emotion"

JFSounds cable is aiming

"High-quality sound x duplicate emotion" design. Expecting to have the emotion as you felt it live in the concert.





"Overwhelming Vibration-damping"

JFSounds continue to develop the Audio Cable with "Vibration damping" as a Key feature.

It is not well known, when Magnesium receives vibration, metal crystals will move and change the vibration into heat energy.

Magnesium will also dampen the vibration.

Magnesion viii also dampon mo vibranon.

Magnesium wire is used in the conductor cable directly and cable itself will have inhibitory effect, which was proven.

Also targeted was the noise reduction effect with new structure conductor.

"Magnesium, Braided shield"

JFSounds have succeeded in making long length and fine Magnesium alloyed wire.

By producing long length and fine sized wire, high shield material Magnesium has managed to be used in the braided shield process and

given success as a braided shield product.

This technology is top class in the world and far ahead of all others.

JFSounds line cable has used Magnesium alloy braided shield.



Audio Line Cable STB27C Type/RCA

Using entire surface with Magnesium material for Original Model

Characteristics

- Original technology from Speaker Cable MS227C was adopted.
- High-shielding was achieved by making the fine magnesium alloy wire braid, which was first in the industry.
- •Plug area is expecting clearer quality sound to be possible with Rhodium-plating.
- By using hollow pipe, distance between conductor is separated and the capacitance is reduced.

Specification

● Structure Conductor 2Core braided shield

structure

Cable Outer Dia: ϕ 9.1mm
• Shield
• ϕ 0.12mm Magnesium Alloy wire

braid


Conductor areaCu2.3sq Total 2.7sq.

Conductor resistance 7.3mΩ/mElectrostatic capacity 137pF/m

● Plug Original RCA plug Material :Brass

Plug processingStabilizerStabilizerOriginal Stabilizer M

Original Stabilizer Material :Brass Surface treatment:Rhodium-plated





Audio Line Cable STB27C-Plus Type/RCA

Targeted clear sound quality for High-End Model

Characteristics

- Using very fine Magnesium alloy wire braid + Hybrid shield with Copper foil suitable for High-End model
- Plug "FURUTECH High-End / Grade RCA Plug FP-108(R)"
- •Pure Magnesium Coil located inside and to pursue cable vibration suppression with original stabilizer.

Specification

Structure Conductor 2Core braided shield structure

● Conductor area Cu2.3sq Total 2.7sq.

Conductor resistance 7.6mΩ/mElectrostatic capacity 131pF/m

● Plug FURUTECH FP-108(R)


Material / Center Pin: α Conductor Body: Cover/Copper Alloy

Plug processing By Screw

Stabilizer Pure Magnesium Coiled Stabilier

Material: Coil/Pure Magnesium

Case: Brass





[JFSounds] is an Audio Brand for Japan Fine Steel Co., Ltd.



Audio Speaker Cable MS227C

Magnesium Wire in the Core material New Idea: Speaker Cable

Characteristics

- ◆Using 99.5% pure magnesium wire in the core area to absorb vibration.
- ullet PC-Triple C ϕ 0.7mm imes 6 stranded structured wire has been used.
- Using Polyethylene pipe material to reduce the capacitance and by reducing the capacitance it will reduce the transmission loss too.
 It is pararellel structure.
- •Polyethylene for insulator.

Specification

Structure7 wire stranded with2 parallel core wire

● Cable Outer Dia 4 × 1 0mm

• Cable Outer Dia 4 × Tomini
• Conductor PC-Triple C 7 ϕ × 6pcs


• Core Conductor Pure Magnesium $0.7 \phi \times 1 pcs$

Conductor Cross Section Cu2.3sq. Total 2.7sq

Electrostatic capacity 36(pF/m)
Conductor resistance 7.8(mΩ/m)



Structure



<"PC-Triple C" Patented in Japan>

Sales agent

●Contact

Japan Fine Steel Co., Ltd. *JFSounds*

19-1,ISHIIDE 1-CHOME SANYOONODA-SHI,YAMAGUCHI,756-0063 JAPAN

TEL:+81 (0) 836-83-4982 FAX:+81 (0) 836-83-2953 E-mail:jfsounds@jpfs.co.jp URL:http://www.jpfs.co.jp/

facebook:https://www.facebook.com/jfsounds/



Audio Line Cable STB27C

Audio Line Cable STB27C-Plus

Audio Speaker Cable MS227C